



# SMART CONNECT

Smart Connect, Smartrise's Inspection Box, comes pre-wired for an easy installation via a Cat-5 cable and seamlessly integrates with all Smartrise Traction and Hydraulic controllers. Located on the top of the car, Smart Connect has pre-drilled mounting brackets with an incandescent light bulb socket.

<b>FIRE SERVICE (BUZZER &amp; JEWEL)</b>	Fire Service 24-28 VDC
<b>TOP-MOUNTED ALARM BELL</b>	Bell 6VDC
<b>DIMENSIONS</b>	4.1"H x 12"W x 6"D
<b>ENCLOSURE RATINGS</b>	NEMA 1, 4, 4x, and 7

## Main Features

- Ceramic Incandescent Light Bulb Socket
- 3-Prong Electrical Cord Duplex Outlet GFCI, 15A 125 VAC
- Pre-Drilled Mounting Holes
- 0.3" Diameter Plastic Service Lamp Guard

## Optional Features

- Metal Service Lamp Guard
- Pushbutton and Switch Safety Guards
- Permanently-Attached Work Light\*

\*Permanently-attached work light with GFCI, lamp, and strain relief. Standard cord lengths is 12-feet. Other lengths can be ordered.

Contact our Sales Department at [sales@smartrise.us](mailto:sales@smartrise.us) to order or for more information.